

MIMAKI'S UNIQUE CORE TECHNOLOGIES ENSURE UNATTENDED, CONTINUOUS PRINTING OPERATION

STABLE PRODUCTION



NCU

Nozzle Check Unit automatically checks nozzle status & executes cleaning cycle when required

NRS

Nozzle Recovery System substitutes defective nozzles to ensure uninterrupted printer operation

$\bigcirc \rightarrow \bigcirc$

UISS Uninterrupted Ink **Supply System** Continuous ink

replenishment through auto-switching of between passes ink packs

HIGH IMAGE QUALITY



MAPS Mimaki Advanced Pass System reduces banding by

dispersing ink drops



VARIABLE DOT

delivers high density print by removing the gap between dots

Print Head		Head assembly, staggered layout
Print Resolution		480dpi, 600dpi, 1,200dpi
Maximum Print Width		1,940mm
Maximum Media Width		1,950mm
Roll Media Weight		45kg
Ink Slots		8
Ink	Type / Colour	Sb610 (BI/Y/M/K/LbI/Lm/Lk/Fy/Fp)*3
	Capacity	2 litre ink pack
Safety standard		VCCI Class A / FCC-class A / Compliant with IEC 62368-1 CE Mark (EMC, Low voltage, Machinery Directive, RoHS) CB Report / REACH / Energy Star / RCM / EA
Interface		Ethernet 1000BASE-T (Recommended) / USB2.0 High Speed
Power		Single phase AC100-120V / AC200-240V x 1
Power consumption		AC100V: 1.44kW / AC200V: 1.92kW or less
Operational environment	Temperature	20 - 30°C
	Humidity	35 - 65%Rh (Non-condensing)
Dimensions (W×D×H)		3,240 x 713 x 1,857mm
Weight		202ka


Lk, Fy and Fp inks available later.


Supplies

Item	Item Code
Sublimation Transfer Ink Sb610 2 litre pack	SB610-x-2L
Sublimation Transfer Ink Sb610 10kg bottle	SB610-x-BJ

For detailed specifications, options and supply list, please visit www.mimakieurope.com


MEUTS5501-EN *Specifications subject to change





HIGH QUALITY OUTPUT AND PRODUCTIVITY

The Mimaki TS55-1800 features a newly developed print head technology that enables the machine to print at 480x600dpi with high ink density using one-pass printing at 140m²/h. In addition, Mimaki's unique Advanced Pass System (MAPS), which eliminates banding, is available from two-pass printing mode.



TxLink 4_{Lite}

10kg Bulk Ink Supply

 $\label{lem:minus} \mbox{Mimaki's } \textbf{TxLink4 dedicated textile RIP software}$

features new functionality and usability improvements.

Parallel RIP and load balancing functions

Boost efficiency by simultaneously performing multiple RIP functions and automatically assign jobs to vacant printers.*1

16-bit rendering

Photographic images and vector graphics are rendered with smooth tonal gradations delivering high quality output, improved colour subtlety and impressive detail.

NEWLY DEVELOPED SB610 INKS

Available in competitively priced 2L packs and low cost 10kg tanks, the new Mimaki Sb610 inks enable businesses to grow profitably and effectively. ECO PASSPORT certified by Oeko-Tex® (an independent verification process demonstrating the safety for use in sustainable textile production), Mimaki Sb610 inks offer strong environmental credentials and high colour yield.

OEKO-TEX®

4-colour mode: • • • 6-colour mode: • •



Available in 10kg tanks and 2litre packs

Only available in 2litre packs

COSTS IN ENTRY AND MID LEVEL SECTORS

With the new, first-in-its-class Mini Jumbo Roll, the TS55-1800 is capable of loading up to 2,500 linear metre of Mimaki Vision Jet-X coated transfer paper (57g/m²). In combination with 10kg ink tanks, the TS55-1800 delivers a new level of efficiency and significantly reduce the cost per square metre. The Mini Jumbo Roll also improves productivity due to reduced media replacement



| Max Weight | Winding: 100kg / Feeding: 300kg | | Max Diameter | Winding: 290mm / Feeding: 600mm | | Max Width | 1,910mm | | Max Printable Width | 1,900mm | | Power | Single Phase AC200-240V x 1 | | Power Consumption | (AC200V) 1.0kW or less | | Dimensions (W×D×H) | Unit Size: 2,770 x 905 x 600mm | Size with main unit: 3,240 x 1,850 x 1,857mm | | Weight | Winding: 100kg / Feeding: 300kg | | Max Weight | Winding: 100kg / Feeding: 300kg | | Max Diameter | Winding: 290mm / Feeding: 600mm | | Max Diameter | Winding: 290mm / Feeding: 600mm | | Max Diameter | Winding: 290mm / Feeding: 600mm | | Max Diameter | Winding: 290mm / Feeding: 600mm | | Max Weight | 1,910mm | | Max Weight | 1,910mm | | Max Weight | 1,910mm | | Max Diameter | Winding: 290mm / Feeding: 600mm | | Max Weight | 1,910mm |

Inkset		4 colours / 6 colours / 7 colours / 8 colours*2		
Ink	Type/Colour	Sb610 (BI/M/Y/K/LbI/Lm/Lk/Fy/Fp)		
	Capacity	10kg ink tank (per colour) Lbl, Lm, Lk, Fy & Fp are supplied in 2L packs		
Dimensions (W×D×H) Unit Size: 824 x 1,035		Unit Size: 824 x 1,035 x 383mm Size with main unit: 4,108 x 1,035 x 1,484mm		
Weight		35kg		
1				

Extended Heater			
Power	Single Phase AC100-120V / AC200-240V x 1		
Power Consumption	(AC100V) 1.0kW or less / (AC200V) 1.0kW or less		
Dimensions (W×D×H)	Unit Size: 2,336 x 108 x 236	Smm Size with main unit: 3,240 x 775 x 1,857mm	
Weight	15kg		
THE RESERVE OF THE PARTY OF THE	The state of the s		

CREATE: Fashion | Sportswear | Apparel | Home Furnishings | Textile Graphics | Point of Sale | Sublimated products | Promotional items | and much more...